



ALPHAROPES[®]

PRODUCT CATALOGUE





MOORING

STRENGTH & TENACITY

ROPES

ROPE GUIDE









SUPERIOR



CONSTRUCTION

- 3 Strand twisted HT Polyester

FEATURES AND USES

- High abrasion resistance
- Mooring line

COLORS

- White
- Navy blue or black
- Other colors on demand

DIAMETERS

6 to 32mm
1/4" to 1 5/16"



MOORING



CONSTRUCTION

- Double braid
- 16 Strand Nylon® Core
- 24 plait polyester cover

FEATURES AND USES

- High stretch, soft handling
- Mooring line

COLORS

- White
- Navy blue or Black
- Other colors on demand

DIAMETERS

8 to 24mm
5/16" to 1"



DOCK LINE



CONSTRUCTION

- Double braid
- 16 Strand HT Polyester Core
- 24 plait polyester cover

FEATURES AND USES

- High loads, soft handling
- Mooring line

COLORS

- White
- Navy blue or Black
- Other colors on demand

DIAMETERS

8 to 24mm
5/16" to 1"



FENDER LINE



CONSTRUCTION

- Single braid
- 24 plait polyester cover

FEATURES AND USES

- Soft handling
- Fenderline

COLORS

- White
- Navy blue or Black
- Other colors on demand

DIAMETERS

8 to 12 mm
1/2" to 51/64"

MOORING

	SUPERIOR	MOORING	DOCKLINE
Ømm/Inch	Kg	Kg	Kg
6mm-1/4"	800		900
8mm-5/16"	1 200		1 350
10mm-3/8"	2 000		2 100
12mm-1/2"	2 900	3 020	2 750
14mm-9/16"	3 700	4 600	4 100
16mm-5/8"	4 400		
18mm-3/4"	6 850	7 000	4 800
20mm-13/16"	7 300		5 400
22mm-7/8"	8 830		6 500
24mm-1"	10 800	12 000	10 500

Superior and Mooring were developed to have an outstanding strength, to be easy to handle and to have a high abrasion resistance.

These lines work perfectly for anchoring, mooring or docking, having superb elongation characteristics that protect your boat from rough weather conditions.

These products are available in spools, coils or packaged factory spliced.

Contact us for further information.



Av. Mosteiro, 486
4415-493 Grijó - Portugal
T. +351 227 476 500 / F. +351 227 646 575
info@alpha-ropes.com / www.alpha-ropes.com

41°01'43.03"N 08°34'59.38"W